Datasheet E-Power Trekking 28 CX6 125 Gent

For more informations visit www.corratec.de



TECHNOLOGIES

DESCRIPTION

- The high-quality aluminum frame offers the highest possible security and stability.
- The newly developed Trinity Tube Edge with its three chamber system is designed for maximum stability and safety.
- Low entry and the ergonomic design enable comfortable riding.

FRAME

| СМ | A | в | c | D | Е | F | G | н | |
|----|-----|-----|----|----|------|-----|-----|-----|--|
| 50 | 605 | 160 | 69 | 73 | 1137 | 465 | 405 | 653 | |
| 55 | 615 | 175 | 69 | 73 | 1148 | 465 | 411 | 667 | |
| 60 | 625 | 190 | 69 | 73 | 1159 | 465 | 417 | 681 | |

EQUIPMENT

MAIN:

FRAME: FORK: BRAKES:

STEM: HANDLEBAR: SEATPOST:

WHEELSET:

RIM:

TIRE:

| Corratec E-Power Trekking 28 |
|--|
| Suntour NEX-E25P 700C |
| Shimano MT 200 front Shimano MT200 rear |
| ZZYZX SL Alloy Stem |
| ZZYZX Trekking Handlebar |
| ZZYZX Alloy Seatpost |

ZZYZX Trekking 29er Disc front

ZZYZX Trekking 29er Disc rear Schwalbe Energizer Active Plus front Schwalbe Energizer Active Plus rear

DRIVE:

CHAINWHEEL: CASSETTE: REAR DERAILLEUR: SHIFT LEVERS: SRAM PG1210 Eagle SRAM CS PG1210 11-50T SRAM SX Eagle SRAM SX Eagle Single Click E Trigger

SPECIAL:

CHAINWHEEL RATIO: CASSETTE RATIO: FORK SUSPENSION TRAVEL: SIZE BRAKE DISC ENGINE: BATTERY: LIGHTS: REAR CARRIER: 1s; 38

12s; 11 13 15 17 19 22 25 28 32 36 42 50

63 mm

180 mm front 160 mm rear BOSCH Performance Line CX BOSCH PowerTube 625Wh AXA Compact Line 20 Massload MIK System Direct Mount Carrier

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.

Rendering is for Reference only.