



Datasheet Revolution iLink Elite

For more informations visit www.corratec.de

R
iLink

Revolution iLink Elite

Frame: Corratec Revolution iLink

Size: 44, 48, 52

Colors:



TECHNOLOGIES

DESCRIPTION

- The perfect bike for allmountain tours and flowy trails.
- iLink TECHNOLOGY – the rear triangle without a separate lockout achieves maximum propulsion.
- The bike, developed according to the Boost standard, generates maximum agility off-road

FRAME

CM	A	B	C	D	E	F	G	H
44	589	101	68	75	1144	435	445	610
48	616	108	68	75	1171	435	460	615
52	632	124	68	75	1192	435	475	630

EQUIPMENT

MAIN:

FRAME:	Corratec Revolution iLink
FORK:	Rockshox Reba Motion Control 29" Boost
FULLY DAMPER:	Rockshox Deluxe Select
BRAKES:	SRAM Guide front SRAM Guide rear
STEM:	ZZYZX SL Alloy Stem
HANDLEBAR:	ZZYZX SL Alloy Handlebar
SADDLE:	Selle Italia Model X
SEATPOST:	Kindshock E20i OD

DRIVE:

CHAINWHEEL:	SRAM NX Eagle Boost Black
CASSETTE:	SRAM PG1230 Eagle
REAR DERAILLEUR:	SRAM NX Eagle
SHIFT LEVERS:	SRAM NX Eagle

WHEELSET:

RIM:	Mavic Crossmax front Mavic Crossmax rear
TIRE:	Schwalbe Hans Dampf

SPECIAL:

CHAINWHEEL RATIO:	1s; 32
CASSETTE RATIO:	12s; 10 12 14 16 18 21 24 28 32 36 42 50
FORK SUSPENSION TRAVEL:	120 mm
SIZE BRAKE DISC	180 mm front 160 mm rear

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.

Rendering is for Reference only