



Datasheet E-Power iLink 180 Race

For more informations visit www.corratec.de

iLINK 180

E-Power iLink 180 Race

Frame: Corratec E-Power iLink 180
Components: Bosch Performance Line CX
Size: 42, 48, 52
Colors:



The rendering is for reference only

TECHNOLOGIES



DESCRIPTION

- **Luxury carbon frame** with 180mm travel.
- **Shadow Edge Tube 2.0** - worldwide most stable and safest corratec E-Bike frame.
- **Inside Link Technology** goes E-MTB.
- **Highest Stiffness** at minimum weight.
- **85 NM** maximum performance.
- **625 WH** maximum range.

FRAME

CM	A	B	C	D	E	F	G	H
42	599	86	65	77	1236	445	455	616
48	611	97	65	77	1248	445	465	621
52	623	106	65	77	1262	445	475	629

EQUIPMENT

MAIN:

FRAME:	Corratec E-Power iLink 180
FORK:	Rockshox Yari Motion Control RC 29" Boost
FULLY DAMPER:	Rockshox Super Deluxe
BRAKES:	Magura MT Thirty front Magura MT Thirty rear
STEM:	ZZYZX SL Alloy
HANDLEBAR:	ZZYZX SL Alloy Handlebar
SADDLE:	Selle Italia Model X
SEATPOST:	Kindshock 900i

DRIVE:

CHAINWHEEL:	SRAM X-SYNC 2 34T
CASSETTE:	SRAM CS PG1210 11-50T
REAR DERAILLEUR:	SRAM GX Eagle Lunar 12S
SHIFT LEVERS:	SRAM SX Eagle Single Click E Trigger

WHEELSET:

RIM:	ZZYZX Cross Attack 29 Boost front ZZYZX Cross Attack 650B rear
TIRE:	Michelin Wild Enduro TLR 29 front Michelin Wild Enduro TLR 650B+ rear

SPECIAL:

CHAINWHEEL RATIO:	1s; 34
CASSETTE RATIO:	12s; 10 12 14 16 18 21 24 28 32 36 42 50
FORK SUSPENSION TRAVEL:	180 mm
SIZE BRAKE DISC:	203 mm front 203 mm rear
ENGINE:	BOSCH Performance Line CX
BATTERY:	BOSCH PowerTube 625Wh

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.