



Datasheet Revolution iLink SL Factory

For more informations visit www.corratec.de

R
iLink

Revolution iLink SL Factory

Frame: Corratec Revolution iLink 29 SL

Size: 44, 48, 52

Colors:



TECHNOLOGIES

DESCRIPTION

- Superlight frame with a weight including damper under 2000gr and a very high torsional stiffness.
- iLink TECHNOLOGY – the rear triangle without a separate lockout achieves maximum propulsion.
- High-quality components ensures best performance on all trails.

FRAME

CM	A	B	C	D	E	F	G	H
44	589	101	68	75	1144	435	445	610
48	616	108	68	75	1171	435	460	615
52	632	124	68	75	1192	435	475	630

EQUIPMENT

MAIN:

FRAME:	Corratec Revolution iLink 29 SL
FORK:	Rockshox SID SL Ultimate 29" Boost
FULLY DAMPER:	Rockshox SID Luxe Ultimate
BRAKES:	SRAM Level Ultimate front SRAM Level Ultimate rear
STEM:	ZZYZX SL Alloy Stem
HANDLEBAR:	ZZYZX SLR Carbon
SADDLE:	Selle Italia Superflow Carbon
SEATPOST:	Rockshox Reverb AXS

DRIVE:

CHAINWHEEL:	SRAM XX1 Eagle DUB
CASSETTE:	SRAM XG1299 Eagle
REAR DERAILLEUR:	SRAM XX1 Eagle AXS 12S
SHIFT LEVERS:	SRAM AXS Eagle

WHEELSET:

RIM:	DT Swiss XCR 1200 Spline front DT Swiss XCR 1200 Spline rear
TIRE:	Schwalbe Racing Ray front Schwalbe Racing Ralph rear

SPECIAL:

CHAINWHEEL RATIO:	1s; 32
CASSETTE RATIO:	12S; 10 12 14 16 18 21 24 28 32 36 42 52
FORK SUSPENSION TRAVEL:	100 mm
SIZE BRAKE DISC	180 mm front 160 mm rear

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.

Rendering is for Reference only.